

## Reach-In Glass Door Refrigerators



TG1R-2HG

Model	Swing Doors	Cu. Ft.	HP	Amps	Crated Weight	Cabinet Dimensions L D† H*
<b>GLASS DOORS</b>						
TG1R-1G	1	31	1/3	9.0	410	29 x 34 <sup>7</sup> / <sub>8</sub> x 78 <sup>1</sup> / <sub>4</sub>
TG2R-2G	2	56	1/2	11.4	710	51 <sup>3</sup> / <sub>8</sub> x 34 <sup>7</sup> / <sub>8</sub> x 78 <sup>1</sup> / <sub>4</sub>
TG3R-3G	3	85	3/4	11.8	867	76 <sup>1</sup> / <sub>2</sub> x 34 <sup>7</sup> / <sub>8</sub> x 78 <sup>1</sup> / <sub>4</sub>
<b>GLASS HALF DOORS</b>						
TG1R-2HG	2	31	1/3	9.0	465	29 x 34 <sup>7</sup> / <sub>8</sub> x 78 <sup>1</sup> / <sub>4</sub>
TG2R-4HG	4	56	1/2	11.4	660	51 <sup>3</sup> / <sub>8</sub> x 34 <sup>7</sup> / <sub>8</sub> x 78 <sup>1</sup> / <sub>4</sub>
<b>COMBINATION HALF DOORS</b>						
TG1R-1HG/1HS	2	31	1/3	9.0	465	29 x 34 <sup>7</sup> / <sub>8</sub> x 78 <sup>1</sup> / <sub>4</sub>
TG2R-2HG/2HS	4	56	1/2	10.0	640	51 <sup>3</sup> / <sub>8</sub> x 34 <sup>7</sup> / <sub>8</sub> x 78 <sup>1</sup> / <sub>4</sub>

All dimensions rounded up to the nearest 1/8".

† Depth does not include 1<sup>3</sup>/<sub>8</sub>" for door handle (glass door models only).

\* Height does not include 5" for castor height or 6" for optional legs.

\* Height does not include 1" for system mechanical components.

*Cabinets shown  
with various tray  
slide options*



TG2R-2HG/2HS

### FEATURES/BENEFITS

- **Shelving** - (3) heavy duty, PVC coated wire shelves per section (4) different interior kits available. (field installation required).
- Oversized and balanced, **environmentally friendly, refrigeration system**, factory sealed and pre-lubricated for long life.
- Food safe refrigerators **hold 33°F to 38°F**.
- **Fluorescent interior lighting**.
- **300 series stainless steel solid doors and front** (the finest stainless available).
- Anodized quality aluminum sides, bottom and back.
- Interior - attractive, **NSF approved**, white aluminum sides and back. **300 series stainless floor and door liner on solid doors**.
- Positive seal self-closing doors with 90 degree stay open feature. **Lifetime guaranteed door hinges**.
- Foamed-in-place polyurethane **high density cell insulation** (CFC free).
- **Energy efficient, "Low-E"**, thermal glass on glass door models.
- Exterior mounted **digital electronic thermometer** features manual defogger.
- **Lifetime guaranteed recessed door handles** on solid doors.
- Door locks standard.
- Extruded, aluminum door frames on glass doors.
- Top mounted unit positioned out of food zone to maximize storage capacity.
- **4" diameter swivel castors** standard equipment. 6" legs available.
- Refrigerator models feature **glass condensate pan** to prevent electrolysis.
- Hot gas condensate for energy efficiency.
- Self-contained system.

Curb mountable units for TR, TA & TG series only. (5% list upcharge)

Remote cabinets available 14% off list (condensing units supplied by others; system comes standard with 404A expansion valve and requires R404A refrigerant). Consult factory technical service dept. for BTU information.